



## Animal Cremation Series

### Model G-30

#### Specifically Designed For :

- Humane Societies
- Animal Control Facilities
- Private Pet Cremation Services
- Veterinary Practices

#### Capacity

#### G-30

#### 3,100 lbs Batch Load Capacity

Easy To Load --- Easy To Operate

22" Load Height

76" Diameter Load Opening

No Visible Emission - No Odors

Meets State And Federal Regulations

No Grease Leakage

Built In Liquid Retention Dam

Built For Long Life

Constructed Of 3/16" Plate Steel, Lined With 1" 1,900 Insulation And 3" Heavy Duty Refractory

Pre- piped & Pre-wired And Assembled At Factory

(Stack Sections Installed On Site)

Automatic Temperature Control For Maximum Efficiency

Fuel Saving Feature Of High - Low Control for Secondary Burner

On - Off Control for Primary Burner

Fuel Saving Preheated Air For Primary & Secondary Chambers

Timer Controls For Burn Cycle



G-30 Shown with Optional Auxiliary Load Door

CONSTRUCTION	G-30-P
Dimensions: W x L x H	95" x 174" x 324"
Primary Chamber Volume	195.2 Cu. Ft.
Stack Sections, 34" x 6' Flanged	Total 18'
(12 Gauge With 3" 2,300°F Refractory Lining)	
Load Door Lined With Hi-Temp Composite	4"
Ash Removal Door Opening	76" Diameter
Primary Burner Firing Rate	2,200,000 BTU Avg.
Secondary Burner Firing Rate	2,400,000 BTU Avg.
Control Panel, NEMA 12, U.L. #508A	Included
Natural Gas Requirements	4,600 CFH
Electrical Requirements	220/60/3 40AMP
Paint & Primer, Hi-Temp	800°F To 1,200°F
Weight	31,299 Pounds

Distributed by:

Bestech Environmental Resources, Inc.

1016 Ronda Lane

Birmingham, Al. 35214

Phone: (205) 791-3656 Fax: (205) 791-6745

www.bestechinc.com – info@bestechinc.com