



Animal Cremation Series

Model G-12

Specifically Designed For:

- Humane Societies
- Animal Control Facilities
- Private Pet Cremation Services
- Veterinary Practices

Capacity

G-12

1,100 lbs Batch Load Capacity

Easy To Load --- Easy To Operate

16" Load Height
60" Diameter Load Opening

No Visible Emission - No Odors

Meets State And Federal Regulations

No Grease Leakage

Built In Liquid Retention Dam

Built For Long Life

Constructed Of 3/16" Plate Steel, Lined With 1 1/2" 1,900 Insulation And 4 1/2" Heavy Duty Refractory

Pre- piped & Pre-wired And Assembled At Factory

(Stack Sections Installed On Site)

Automatic Temperature Control For Maximum Efficiency

Fuel Saving Feature Of High - Low Control for Secondary Burner

On - Off Control for Primary Burner

Fuel Saving Preheated Air For Primary & Secondary Chambers

Timer Controls for Burn Cycle



CONSTRUCTION	G-12-P
Dimensions: W x L x H	78" x 102" x 313"
Primary Chamber Volume	75.59 Cu. Ft.
Stack Sections, 22" x 6' Flanged	Total 18'
(12 Gauge With 3" 2,300°F Refractory Lining)	
Load Door Lined With Hi-Temp Composite	4 1/2"
Ash Removal Door Opening	48" Diameter
Primary Burner Firing Rate	900,000 BTU Avg.
Secondary Burner Firing Rate	900,000 BTU Avg.
Control Panel, NEMA 12, U.L. #508A	Included
Natural Gas Requirements	1800 CFH
Electrical Requirements	220/60/1/20AMP 110/60/1/40AMP
Paint & Primer, Hi-Temp	800°F To 1,200°F
Weight	15,203 Pounds

Recommended Room or Pad with
Fence Size: 18' x 20'

Recommended Pad Size: 12' x 16'

Distributed by:

Bestech Environmental Resources, Inc.
138 Industrial Park Drive
Woodstock, AL 35188
Phone: (205) 428-0210 Fax: (205) 428-0211
www.bestechinc.com – info@bestechinc.com