



## Animal Cremation Series

### Model G-16

**Specifically Designed For :**

- Humane Societies
- Animal Control Facilities
- Private Pet Cremation Services
- Veterinary Practices

### Capacity

#### G-16

#### 1,400 lbs Batch Load Capacity

Easy To Load --- Easy To Operate

16" Load Height

60" Diameter Load Opening

No Visible Emission - No Odors

Meets State And Federal Regulations

No Grease Leakage

Built In Liquid Retention Dam

Built For Long Life

Constructed Of 3/16" Plate Steel, Lined With 1" 1,900 Insulation And 3" Heavy Duty Refractory

Pre-piped & Pre-wired And Assembled At Factory

(Stack Sections Installed On Site)

Automatic Temperature Control For Maximum Efficiency

Fuel Saving Feature Of High - Low Control for Secondary Burner

On - Off Control for Primary Burner

Fuel Saving Preheated Air For Primary & Secondary Chambers

Timer Controls For Burn Cycle



CONSTRUCTION	G-16-P
Dimensions: W x L x H	78" x 114" x 313"
Primary Chamber Volume	85.22 Cu. Ft.
Stack Sections, 22" x 6' Flanged	Total 18'
(12 Gauge With 3" 2,300°F Refractory Lining)	
Load Door Lined With Hi-Temp Composite	4"
Ash Removal Door Opening	60" Diameter
Primary Burner Firing Rate	1,200,000 BTU Avg.
Secondary Burner Firing Rate	1,200,000 BTU Avg.
Control Panel, NEMA 12, U.L. #508A	Included
Natural Gas Requirements	2,400 CFH
Electrical Requirements	220/60/1 20AMP
Paint & Primer, Hi-Temp	800°F To 1,200°F
Weight	16,373 Pounds

Recommended Room or Pad with  
Fence Size: 18' x 20'  
  
Recommended Pad Size: 12' x 17'

Distributed by:  
  
**Bestech Environmental Resources, Inc.**  
138 Industrial Park Drive  
Woodstock, AL 35188  
Phone: (205) 428-0210 Fax: (205) 428-0211  
www.bestechinc.com – info@bestechinc.com