



## Animal Cremation Series

### Model G-30

#### Specifically Designed For :

Humane Societies  
 Animal Control Facilities  
 Private Pet Cremation Services  
 Veterinary Practices

#### Capacity

#### G-30

#### 3,000 lbs Batch Load Capacity

Easy To Load --- Easy To Operate

22" Load Height

76" Diameter Load Opening

No Visible Emission - No Odors

Meets State And Federal Regulations

No Grease Leakage

Built In Liquid Retention Dam

Built For Long Life

Constructed Of 3/16" Plate Steel, Lined With 1" 1,900 Insulation And 3" Heavy Duty Refractory

Pre- piped & Pre-wired And Assembled At Factory

(Stack Sections Installed On Site)

Automatic Temperature Control For Maximum Efficiency

Fuel Saving Feature Of High - Low Control for Secondary Burner

On - Off Control for Primary Burner

Fuel Saving Preheated Air For Primary & Secondary Chambers

Timer Controls For Burn Cycle



G-30 Shown with Optional Auxiliary Load Door

| CONSTRUCTION                                 | G-30-P             |
|--|--------------------|
| Dimensions: W x L x H                        | 95" x 174" x 324"  |
| Primary Chamber Volume                       | 195.2 Cu. Ft.      |
| Stack Sections, 34" x 6' Flanged             | Total 18'          |
| (12 Gauge With 3" 2,300°F Refractory Lining) |                    |
| Load Door Lined With Hi-Temp Composite       | 4"                 |
| Ash Removal Door Opening                     | 76" Diameter       |
| Primary Burner Firing Rate                   | 1,750,000 BTU Avg. |
| Secondary Burner Firing Rate                 | 2,200,000 BTU Avg. |
| Control Panel, NEMA 12, U.L. #508A           | Included           |
| Natural Gas Requirements                     | 4,600 CFH          |
| Electrical Requirements                      | 220/60/3 40AMP     |
| Paint & Primer, Hi-Temp                      | 800°F To 1,200°F   |
| Weight                                       | 31,299 Pounds      |

Distributed by:

Bestech Environmental Resources, Inc.  
 138 Industrial Park Drive  
 Woodstock, AL 35188  
 Phone: (205) 428-0210 Fax: (205) 428-0211  
 www.bestechinc.com – info@bestechinc.com