



Animal Cremation Series

Model S-18

Specifically Designed For :

- Humane Societies
- Animal Control Facilities
- Private Pet Cremation Services
- Veterinary Practices

Capacity S-18

300 lbs Batch Load Capacity

Easy To Load --- Easy To Operate

16" Load Height

22" x 26" Load Opening

No Visible Emission - No Odors

Meets State And Federal Regulations

No Grease Leakage

Built In Liquid Retention Dam

Built For Long Life

Constructed Of 10 Ga. Steel, Lined With 1" 1,900 Insulation And 3" Heavy Duty Refractory

Pre-piped & Pre-wired And Assembled At Factory

(Stack Sections Installed On Site)

Automatic Temperature Control For Maximum Efficiency

High - Low Control for Secondary Burner

On - Off Control for Primary Burner

Fuel Saving Preheated Air For Primary & Secondary Chambers



CONSTRUCTION	S-18
Dimensions: W x L x H	37"x 64"x73"
Primary Chamber Volume	18.33
Stack Sections, 20" x 6' Flanged	Total 18'
(12 Gauge With 3" 2,300°F Refractory Lining)	
Load Door Lined With Hi-Temp Composite	4"
Load Door / Clean Out Door Size	26" x 22"
Primary Burner Firing Rate	400,000 Avg.
Secondary Burner Firing Rate	450,000 Avg.
Control Panel, NEMA 12, U.L. #508A	Included
Natural Gas Requirements	850 CFH
Electrical Requirements	115/60/1 30AMP
Paint & Primer, Hi-Temp	800°F To 1,200°F
Weight	6,944 Pounds

Recommended Pad Size: 8'x12'
 Recommended Room or Pad with
 Fence Size: 12'x16'

Distributed by:
 Bestech Environmental Resources, Inc.
 138 Industrial Park Drive
 Woodstock, AL 35188
 Phone: (205) 428-0210 Fax: (205) 428-0211
 www.bestechinc.com – info@bestechinc.com