



Animal Cremation Series

Model S-27-T

Specifically Designed For :

- Humane Societies
- Animal Control Facilities
- Private Pet Cremation Services
- Veterinary Practices

Capacity

S-27-T

450 lbs Batch Load Capacity

Easy To Load --- Easy To Operate

31" Load Height

28" x 31" Load Opening

No Visible Emission - No Odors

Meets State And Federal Regulations

No Grease Leakage

Built In Liquid Retention Dam

Built For Long Life

Constructed Of 3/16" Plate Steel, Lined With 1" 1,900 Insulation And 3" Heavy Duty Refractory

Pre- piped & Pre-wired And Assembled At Factory

(Stack Sections Installed On Site)

Automatic Temperature Control For Maximum Efficiency

Fuel Saving Feature Of High - Low Control for Secondary Burner

On - Off Control for Primary Burner

Fuel Saving Preheated Air For Primary & Secondary Chambers

Timer Controls For Burn Cycle



CONSTRUCTION	S-27-T
Dimensions: W x L x H	56" x 84" x 80"
Primary Chamber Volume	29 CFT
Stack Sections, 20" x 6' Flanged	Total 12'
(12 Gauge With 3" 2,300°F Refractory Lining)	
Load Door Lined With Hi-Temp Composite	4"
Ash Removal Door Opening	18" x 10"
Primary Burner Firing Rate	400,000 BTU Avg.
Secondary Burner Firing Rate	450,000 BTU Avg.
Control Panel, NEMA 12, U.L. #508A	Included
Natural Gas Requirements	850 CFH
Electrical Requirements	115/60/1 30AMP
Paint & Primer, Hi-Temp	800°F To 1,200°F
Weight	7,676 Pounds

Recommended Open Pad Size: 10'x12'
 Recommended Room Pad Size: 15'x15'

Distributed by:

 Bestech Environmental Resources, Inc.
 138 Industrial Park Drive
 Woodstock, AL 35188
 Phone: (205) 428-0210 Fax: (205) 428-0211
 www.bestechinc.com – info@bestechinc.com