



## Animal Cremation Series

### Model S-27-GF

Specifically Designed For :

- Private Pet Cremation Services
- Veterinary Practices
- Animal Control Facilities
- Humane Societies

### Capacity

#### S-27-GF

#### 200 lbs Batch Load Capacity

**Power Operated Vertical Door**

Lined With High Temperature Composite Ceramic Fiber

**Easy To Load --- Easy To Operate**

23" Load Height Front Ash Removal

22" x 26" Load Opening

**No Visible Emission - No Odors**

Meets State And Federal Regulations

**No Liquid Leakage**

Built In Liquid Retention With 3" Slope To Back Of Tile Hearth

**Built For Long Life**

Constructed Of 3/16" Plate Steel, Lined With 1" 1,900 Insulation And 3" Heavy Duty Refractory

**Pre-piped & Pre-wired And Assembled At Factory**

Shipment Of Main Chamber And Secondary Chamber Fully Assembled

Two Stack Sections Included - Installed At Jobsite

**Automatic Temperature Control For Maximum Efficiency**

Fuel Saving Feature Of High - Low Control for Secondary Burner

On - Off Control for Primary Burner



CONSTRUCTION	S-27-GF
Dimensions: W x L x H	48" x 90" x 81"
Primary Chamber Volume	27 CFT
Stack Sections, Two Each, 20" x 6' Flanged	Total 12'
10 Gauge With 3" 2,300°F Refractory Lining Load Door Lined With Hi-Temp Composite	
Load Door Opening	26" x 22"
Load Door - Outside Dimensions	32" x 35.5"
Ash Removal Drawer	14" x 9.5"
Primary Burner Firing Rate	375,000 BTU Avg.
Secondary Burner Firing Rate	375,000 BTU Avg.
Control Panel, NEMA 12, U.L. #508A	Included
Natural Gas/Propane Requirements	800 CFH
Optional #2 Fuel Oil 5.8 GPH Electrical Requirements	115/60/1 30AMP
Paint & Primer, Hi-Temp	800°F To 1,200°F
Weight Pounds	6,500

Recommended Pad Size: 10'x12'  
Recommended Room or Pad with Fence Size: 15'x15'

Distributed By:  
Bestech Environmental Resources, Inc.  
138 Industrial Park Drive  
P.O. Box 189  
Woodstock, Alabama 35188  
1-800-871-9005